

Liquid Filtration

3M Ultra High Loft Liquid Filter Bags



Available Micron Ratings

1, 5, 10, 25, 50 and 100

Materials of Construction and Design

- 100% Polypropylene needle felt
- Ultra High Loft media
- Fibre free surface treatment
- Thermally welded
- Silicon free manufacture
- Positive seal plastic sealing ring/handle
- Fits most vessels
- Rounded bottom
- 7" Diameter by 32" length (P2)
- Max. temperature – 200 F
- Max. differential pressure – 25 psi

Features, Advantages and Benefits

Polypropylene media is selected based on performance and consistency to ensure reliable filtration performance. The media is surface treated to prevent fibre contamination downstream.

The Ultra High Loft felt media increases the filtration media surface area to increase filter life up to 5X dependent upon application

The plastic retainer ring design ensures a positive seal with most filter vessels to ensure bypass free filtration. The ring also acts as a handle for quick bag removal.

The rounded bottom weld configuration ensures a better and more flexible fit to the retainer basket for more support as pressure builds.

The thermal bonding process ensures, bypass free, thread free seams to ensure filtration efficiencies.

The 100% polypropylene construction offers broad chemical compatibility. Consult a plastic resin chemical compatibility chart to ensure appropriate media selection.

The end result is a durable, consistently performing, low cost filter for low flow applications where nominal filtration is all that you need. For higher flow more efficient applications, 3M Series 500 High Efficiency Bags or 3M Sapphire cartridges are recommended.

Important Notice to Purchaser

The information in this publication is based on tests that we believe are reliable. Your results may vary due to differences in test types and conditions. You must evaluate and determine whether the product is suitable for your intended application. Since conditions of product use are outside of our control and vary widely, the following is made in lieu of all express or implied warranties (including the warranties of merchantability or fitness for a particular purpose): 3M's only obligation and your only remedy is replacement of product that is shown to be defective when you receive it. In no case will 3M be liable for any special, incidental, or consequential damages based on breach of warranty or contract, negligence, strict tort, or any other theory.

Specialty Materials/Filtration Products

3M Canada Company

P.O. Box 5757

London, Ontario N6A 4T1

519-451-2500 1-800-265-1840

