

Liquid Filtration

3M Standard Polyester Felt Liquid Filter Bags



Available Sizes

P1 – 7" x 16.5"
P2 – 7" x 32"

Available Micron Ratings

1, 5, 10, 25, 50,
75, 100 and 200

Materials of Construction and Design

- 100% Polyester needle felt
- Fibre free surface treatment
- Thermally welded
- Steel Ring retainer
- Designed with no seam lump on ring
- Silicon free manufacture
- Fits most vessels
- Integral handles for easy changeout.
- Rounded bottom to improve fit
- Max. temperature – 275 F
- Max. differential pressure – 25 psi
- FDA Approved

Features, Advantages and Benefits

Polyester media is selected based on performance and consistency to ensure reliable filtration performance. The media is surface treated to prevent fibre contamination downstream.

The rounded bottom weld configuration ensures a better and more flexible fit to the retainer basket for more support as pressure builds.

The thermal bonding process ensures, bypass free, thread free seams to ensure filtration efficiencies.

The no-lump, no seam steel retainer ring design ensures there is no bypass

The polyester/steel construction offers broad chemical compatibility. Consult a plastic resin chemical compatibility chart to ensure appropriate media selection.

The end result is a durable, consistently performing, low cost filter for low flow applications where nominal filtration is all that you need. For higher flow more efficient applications, 3M Series 500 High Efficiency Bags or 3M Sapphire cartridges are recommended.

Important Notice to Purchaser

The information in this publication is based on tests that we believe are reliable. Your results may vary due to differences in test types and conditions. You must evaluate and determine whether the product is suitable for your intended application. Since conditions of product use are outside of our control and vary widely, the following is made in lieu of all express or implied warranties (including the warranties of merchantability or fitness for a particular purpose): 3M's only obligation and your only remedy is replacement of product that is shown to be defective when you receive it. In no case will 3M be liable for any special, incidental, or consequential damages based on breach of warranty or contract, negligence, strict tort, or any other theory.

Specialty Materials/Filtration Products
3M Canada Company
P.O. Box 5757
London, Ontario N6A 4T1
519-451-2500 1-800-265-1840

